

## **Product** Datasheet

www.1-light.eu

#### New 2020 Edition 2>Downlights Fixed LED

### 10110U/W/C




10W SMD LED UGR19 downlight, IP44.

Complete with 200mA driver.

Complies with standard EN60598-1 and any other specific standards.







#### Gallery



#### **Physical Specification**

Item Group

New 2020 Edition 2

|   |            |              | ••• |          |
|---|------------|--------------|-----|----------|
| _ | $\gamma$ r | $\mathbf{n}$ |     | <b>`</b> |
|   | ar         |              |     | v        |
|   | u          |              |     | y        |
|   |            |              |     | ,        |

#### Downlights Fixed LED

| Order Code | 10110U/W/C |
|------------|------------|
| Colour     | White      |
| Material   | Die Cast   |
| Shape      | Circular   |
| Height     | 35mm       |



| Diameter             | 95mm |
|----------------------|------|
| Cutout Hole Diameter | 86mm |
| Recessed Ceiling     | Yes  |
| Depth Required       | 55mm |
| Indoor               | Yes  |
| Adjustable           | No   |

#### Electrical Characteristics

| Gear             | External-Included |
|------------------|-------------------|
| Fitting + Driver |                   |
| Input Voltage    | 220-240V          |
| 50 Hz            | Yes               |
| 60 Hz            | Yes               |
| Safety Class     |                   |
| Power(Watts)     | 10W               |
| IP Rating        | IP44              |
| Light Source     | LED built in      |
| Dimmable         | No                |
| F Mark           | F                 |
|                  |                   |

| Fitting       |                  |
|---------------|------------------|
| Input Type    | Constant Current |
| Input Current | 200mA            |
| Voltage       | 38V              |
|               | $\land$          |

| Safety Class |              |
|--------------|--------------|
| Power(Watts) | 9,6W         |
| IP Rating    | IP44         |
| Light Source | LED built in |
| LED Type     | SMD 2835     |
| LED Brand    | Epistar      |
|              |              |



| Gear             |                            |
|------------------|----------------------------|
| Gear Type        | Led Driver                 |
| Input Voltage    | 220-240V                   |
| 50 Hz            | Yes                        |
| 60 Hz            | Yes                        |
| Power(Watts)     | 5,4-8,4W                   |
| Power Factor     | 0,9                        |
| Constant Current | Yes                        |
| 200mA            | 27-42V                     |
| IP Rating        | IP44                       |
| Safety Class     |                            |
| Dimmable         | No                         |
| Housing Material | Plastic                    |
| Output Terminal  | Cable                      |
| Brand            | Lifud                      |
| Protection       | Short Circuit and Overload |

#### Illumination Data


| Colour Temperature   | 4000K  |
|----------------------|--------|
| Lumen Output         | 750lm  |
| Light Efficiency     | 75lm/W |
| CRI                  | 80     |
| Illumination Diagram |        |

#### Packing Info

| Pcs/Carton | 40            |
|------------|---------------|
| Barcode    | 5291889065340 |



#### Energy Label



#### Certification & Warranty

| Warranty         | 3 Years  |
|------------------|----------|
| Average Lifetime | 30000hrs |
| Weee Directive   | Yes      |

# switch to one light!



