



# **Product Datasheet**

New 2020 Edition 2>Downlights Fixed LED

# 10110U/W/W



10W SMD LED UGR19 downlight, IP44.

Complete with 200mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions





#### Gallery




#### **Physical Specification**

Item Group	New 2020 Edition 2
Family	Downlights Fixed LED
Order Code	10110U/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	35mm

Diameter	95mm
Cutout Hole Diameter	86mm
Recessed Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	200mA
Voltage	38V
Safety Class	
Power(Watts)	9,6W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	5,4-8,4W
Power Factor	0,9
Constant Current	Yes
200mA	27-42V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload
Ilumination Data	
Colour Tomorovatura	200014
Colour Temperature	3000K
Light Efficiency	750lm 75lm/M
Light Efficiency	75lm/W 80
CRI	00 
Illumination Diagram	10
UGR	19
Packing Info	
Pcs/Carton	40
Barcode	5291889065333

## Energy Label



### Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to one light!

