


06 Downlights Fixed LED > Round Recessed Panels

10120F/G/D



30W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms.

Supplied with 1000mA non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads



Dimensions



Gallery






Physical Specification


Item Group	06 Downlights Fixed LED
Family	Round Recessed Panels
Order Code	10120F/G/D
Colour	Grey
Material	Die Cast
Diffuser Material	Acrylic
Shape	Circular

Height	20mm
Diameter	300mm
Cutout Hole Diameter	285mm
Recessed Ceiling	Yes
Depth Required	40mm
Indoor	Yes
Adjustable	No


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	28V
Safety Class	
Power(Watts)	28W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2016

LED Brand	Epistar
LED Number	208
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	23-28W
Power Factor	0,9
Constant Current	Yes
1000mA	23-28V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	85°C
Housing Material	Plastic
Manufacturer	One Light
Protection	Open Circuit/Short Circuit


Illumination Data

Colour Temperature	6000K
Lumen Output	1997lm
Light Efficiency	66,56lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	38cm
Box Width	31cm
Box Height	3cm
Box Weight	1,13Kg
Pcs/Carton	10
Barcode	5291889034988
HS Code	9405109890

Energy Label



Certification & Warranty

Warranty	2 Years
Average Lifetime	30000 hours
Weee Directive	Yes

switch to
one light!

one
LIGHT

