

Product Datasheet

www.1-light.eu

New 2020 Edition 2>Downlights Fixed LED

10120UV/W



20W SMD LED UGR19 downlight with adjustable CCT, IP44.


Complete with 550mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads

Dimensions



Gallery



Physical Specification

Item Group

New 2020 Edition 2

			•••	
_	γ r	\mathbf{n}		`
	ar			v
	u			y
				,

Downlights Fixed LED

Order Code	10120UV/W
Colour	White
Material	Die Cast
Shape	Circular
Height	55mm



Diameter	190mm
Cutout Hole Diameter	170mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting	
Input Type	Constant Current
Input Current	550mA
Voltage	36V

Safety Class	
Power(Watts)	19,8W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar



Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13,75-22W
Power Factor	0,9
Constant Current	Yes
550mA	25-40V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload

Illumination Data


Colour Temperature	3000-4000K-6000K
Lumen Output	1500lm
Light Efficiency	75lm/W
CRI	80
Illumination Diagram	

Packing Info

Pcs/Carton	20
Barcode	5291889065319



Energy Label



Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to one light!



