



Product Datasheet

06 Downlights Fixed LED>The Budget Downlight Range

10124T/W/C



24W SMD LED recessed downlight, budget range, IP20.

Complete with 600mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions





— 55mm

Gallery





Physical Specification

Item Group
Family
Order Code
Colour
Material
Shape
Height

06 Downlights Fixed LED

The Budget Downlight Range

10124T/W/C

White

Aluminium

Circular


55mm

Diameter	235mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	75mm
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	36V
Safety Class	
Power(Watts)	21,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan

LED Number	48
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	14,5-23,2W
Power Factor	0,95
Constant Current	Yes
600mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Kegu
Illumination Data	
Colour Tomporatura	4000K
Colour Temperature	4000K 1800lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	
murimation Diagram	
Packing Info	
Box Length	24,5cm
Box Width	24,5cm

Box Height	6cm
Box Weight	0,64kg
Pcs/Carton	20
Barcode	5291889045823
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to one light!

