



Product Datasheet

New 2020 Edition 2>Downlights Fixed LED

10124U/W/C



24W SMD LED UGR19 downlight, IP44.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery




Physical Specification

| Item Group | New 2020 Edition 2 |
|------------|----------------------|
| Family | Downlights Fixed LED |
| Order Code | 10124U/W/C |
| Colour | White |
| Material | Die Cast |
| Shape | Circular |
| Height | 35mm |
| | |

| Diameter | 170mm |
|---------------------------|-------------------|
| Cutout Hole Diameter | 160mm |
| Recessed Ceiling | Yes |
| Depth Required | 55mm |
| Indoor | Yes |
| Adjustable | No |
| | |
| lectrical Characteristics | |
| | |
| Gear | External-Included |
| Fitting + Driver | |
| | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 24W |
| IP Rating | IP44 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | F |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 500mA |
| Voltage | 40V |
| Safety Class | |
| Power(Watts) | 20W |
| IP Rating | IP44 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Epistar |
| | |

| F Mark | F |
|----------------------|----------------------------|
| | |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 12,5-20W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 500mA | 25-40V |
| IP Rating | IP44 |
| Safety Class | |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | Lifud |
| Protection | Short Circuit and Overload |
| | |
| Illumination Data | |
| Colour Temperature | 4000K |
| Lumen Output | 1800lm |
| Light Efficiency | 75lm/W |
| CRI | 80 |
| Illumination Diagram | |
| UGR | 19 |
| | |
| Dealing late | |
| Packing Info | |
| Pcs/Carton | 20 |
| Barcode | 5291889065364 |

Energy Label



Certification & Warranty

| Warranty | 3 Years |
|------------------|----------|
| Average Lifetime | 30000hrs |
| Weee Directive | Yes |

switch to one light!

