



Product Datasheet

New 2020 Edition 2>Downlights Fixed LED

10124U/W/W



24W SMD LED UGR19 downlight, IP44.

Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery




Physical Specification

Item Group	New 2020 Edition 2
Family	Downlights Fixed LED
Order Code	10124U/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	35mm

Diameter	170mm
Cutout Hole Diameter	160mm
Recessed Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	40V
Safety Class	
Power(Watts)	20W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	12,5-20W
Power Factor	0,9
Constant Current	Yes
500mA	25-40V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload
Illumination Data	
Colour Temperature	3000K
Lumen Output	1800lm
Light Efficiency	75lm/W
CRI	80
Illumination Diagram	
UGR	19
Dealing late	
Packing Info	
Pcs/Carton	20
Barcode	5291889065357

Energy Label



Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to one light!

