

06 Downlights Fixed LED>The IP54 Bathroom Downlights

10125B/W/C



25W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery






Physical Specification


Item Group	06 Downlights Fixed LED
Family	The IP54 Bathroom Downlights
Order Code	10125B/W/C
Colour	White
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular

Height	46mm
Diameter	228mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Outdoor	Yes
Adjustable	No


Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	


Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	32V
Safety Class	
Power(Watts)	22,5W
IP Rating	IP54
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	60
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	16,8-26,6W
Power Factor	0,9
Constant Current	Yes
700mA	24-38V
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	70°C
Housing Material	Plastic
Output Terminal	Cable
Manufacturer	0
Protection	Short Circuit and Overload


Illumination Data

Colour Temperature	4000K
Lumen Output	2000lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Length	26cm
Box Width	26cm
Box Height	7,5cm
Box Weight	1,2Kg
Pcs/Carton	10
Barcode	5291889043232
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes

switch to
one light!

one
LIGHT

