



## **Product Datasheet**

06 Downlights Fixed LED>The COB Downlight Range Aluminium

### 10130CR/W/W



30W COB LED recessed downlight, IP20.

Complete with 850mA driver.

Complies with standard EN60598-1 and any other specific standards.




Downloads







Dimensions




#### **Physical Specification**

Product Type	Gear
Item Group	06 Downlights Fixed LED
Family	The COB Downlight Range Aluminium
Order Code	10130CR/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	70mm
Diameter	230mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	120mm

Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	850mA
Voltage	33V
Safety Class	
Power(Watts)	28W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Epistar
F Mark	F
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	20,4-41,6W
Power Factor	0,9
Constant Current	Yes
850mA	24-49V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Ilumination Data	
Colour Temperature	3000K
Lumen Output	2200lm
Light Efficiency	73,33lm/W
CRI	90
Beam Angle	80°
Illumination Diagram	
Packing Info	
Box Length	26cm
Box Length  Box Width	26cm 26cm
Box Width	26cm
Box Width  Box Height	26cm 9,5cm
Box Width  Box Height  Box Weight	26cm 9,5cm 1,22kg
Box Width  Box Height  Box Weight  Pcs/Carton	26cm 9,5cm 1,22kg



#### Certification & Warranty

Warranty	2 Years
Wee Directive	Yes

# switch to one light!

