



# **Product Datasheet**

### 04 Recessed Spots Adjustable LED>The COB Round Spots

## 11106A/AL/C



COB LED recessed spot. Very elegant design with unique design of the reflector. Ideal for replacing halogen spots.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads









Dimensions




#### **Physical Specification**

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Round Spots
Order Code	11106A/AL/C
Colour	Aluminium
Material	Aluminium
Shape	Circular
Height	61mm
Diameter	92mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes

#### Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	500mA
Voltage	12V
Safety Class	III
Power(Watts)	6W
IP Rating	IP20
Light Source	LED built in
LED Brand	Citizen
LED Number	1
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	100-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-9W
Power Factor	0,9
Constant Current	Yes
500mA	12-18
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~50°C
Housing Material	Plastic
Output Terminal	Cable
Brand	HEP
Illumination Data	
Colour Temperature	4000K
Lumen Output	485lm
Lumen Output Light Efficiency	485lm 80,83lm/W
Lumen Output  Light Efficiency  CRI	485lm 80,83lm/W 80
Lumen Output  Light Efficiency  CRI  Beam Angle	485lm 80,83lm/W
Lumen Output  Light Efficiency  CRI	485lm 80,83lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle	485lm 80,83lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle	485lm 80,83lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	485lm 80,83lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	485lm 80,83lm/W 80 36°
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length	485lm 80,83lm/W 80 36°  11,5cm
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width	485lm 80,83lm/W 80 36°  11,5cm 9cm
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height	485lm 80,83lm/W 80 36°  11,5cm 9cm 11,5cm
Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Length  Box Width  Box Height  Pcs/Carton	485lm 80,83lm/W 80 36°  11,5cm 9cm 11,5cm



#### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

# switch to one light!

