

04 Recessed Spots Adjustable LED>The COB Dark Light Range

11107FD/W/C



7W COB LED Adjustable Dark Light recessed spot IP20.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery




Physical Specification


Item Group	04 Recessed Spots Adjustable LED
Family	The COB Dark Light Range
Order Code	11107FD/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	83mm

Diameter	95mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	21V
Safety Class	
Power(Watts)	6,2W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Epistar

LED Number	1
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,2-7,2W
Power Factor	0,9
Constant Current	Yes
300mA	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud

Illumination Data


Colour Temperature	4000K
Lumen Output	560lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	11,5cm
Box Width	10cm
Box Height	11,5cm

Box Weight	0,281Kg
Pcs/Carton	50
Barcode	5291889052104
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Weee Directive	Yes

switch to
one light!

one
LIGHT

