



Product Datasheet

04 Recessed Spots Adjustable LED>Moving Inner Cylinder Range

11110B/W/C



10W COB LED recessed adjustable spot, for general lighting applications.

Complete with driver.

Complies with standard EN60598-1 and any other specific standards.















Downloads










Dimensions



Gallery



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	Moving Inner Cylinder Range
Order Code	11110B/W/C
Colour	White
Material	Aluminium
Shape	Circular
Height	134mm

Diameter	136mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	38V
Safety Class	
Power(Watts)	9,5W
IP Rating	IP20
Light Source	LED built in
LED Type	COB


Cree

LED Brand

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8-10W
Power Factor	0,55
Constant Current	Yes
250mA	32-40V
IP Rating	IP20
Safety Class	
Housing Material	Plastic
Brand	Philips
Illumination Data	
Colour Temperature	4000K
	4000K 750lm
Colour Temperature	
Colour Temperature Lumen Output	750lm
Colour Temperature Lumen Output Light Efficiency	750lm 75lm/W
Colour Temperature Lumen Output Light Efficiency CRI	750lm 75lm/VV 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	750lm 75lm/VV 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	750lm 75lm/W 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	750lm 75lm/W 80 36°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	750lm 75lm/W 80 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	750lm 75lm/W 80 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info	750lm 75lm/W 80 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	750lm 75lm/W 80 36° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length Box Width	750lm 75lm/W 80 36° Yes 18,5cm

Pcs/Carton 12 Barcode 5291889047711 **HS** Code 9405409900

Energy Label



Certification & Warranty

Warranty 3 Years

Weee Directive Yes

switch to one light!

