\mathbf{e}

Product Datasheet

www.1-light.eu

New 2020 Edition 2>Recessed Spots Adjustable LED

11110E/B/W




10W COB LED adjustable recessed Spot with dark chrome reflector.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads		Dimensions	Dimensions	
IES	ο τε	95mm		



Physical Specification

Item Group	New 2020 Edition 2
Family	Recessed Spots Adjustable LED
Order Code	11110E/B/W
Colour	Black
Material	Die Cast
Shape	Circular
Height	50mm

Diameter	95mm
Cutout Hole Diameter	85mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes



1 Direction

Electrical Characteristics

Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	250mA
Voltage	35,5V
Safety Class	
Power(Watts)	8,9W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ

LED Brand	Cree
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V




50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,25-10,5W
Power Factor	0,9
Constant Current	Yes
250mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	850lm
Light Efficiency	85lm/W
CRI	80
Beam Angle	30°
Illumination Diagram	
Dark Light	Yes

Packing Info	
Pcs/Carton	40
Barcode	5291889064190

9405409900







Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to one light!



