

08 Downlights Adjustable LED>The COB Pop Out Range

11125RA/W/C



25W COB LED recessed adjustable spot, for general lighting applications.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	08 Downlights Adjustable LED
Family	The COB Pop Out Range
Order Code	11125RA/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	125mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	2 Directions

Gear

External-Included

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class



Power(Watts)

25W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

700mA

Voltage

40V

Safety Class



Power(Watts)

28W

IP Rating

IP20

Light Source

LED built in

LED Type

COB

LED Brand

Bridgelux

F Mark



Gear

Gear Type

Led Driver

Input Voltage


220-240V

50 Hz


Yes

60 Hz

Yes

Power(Watts)	18-30W
Power Factor	0,9
Constant Current	Yes
700mA	25.5-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	80°C
Housing Material	Plastic
Brand	Eaglerise
Protection	Short circuit Protection

Illumination Data

Colour Temperature	4000K
Lumen Output	1900lm
Light Efficiency	76lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	20,5cm
Box Width	15cm
Box Height	15cm
Box Weight	1Kg
Pcs/Carton	12
Barcode	5291889047766
HS Code	9405409900



Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

