



Product Datasheet

08 Downlights Adjustable LED>The COB Retro Downlights

11130C/W/C



30W COB LED recessed adjustable spot, for general lighting applications.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads









Dimensions





85mm

Gallery





Physical Specification

Item Group	
Family	
Order Code	
Colour	
Material	
Shape	
Height	

08 Downlights Adjustable LED

The COB Retro Downlights

11130C/W/C

White

Aluminium

Circular

85mm

Diameter	158mm
Cutout Hole Diameter	145mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	1 Direction
Electrical Characteristics	
Gear	External-Included
Fitting & Driver	
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	39V
Safety Class	<u> </u>
Power(Watts)	27,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB


LED Brand	Sanan
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30W
Power Factor	0,9
Constant Current	Yes
700mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Manufacturer	Lifud
Ilumination Data	
Colour Temperature	4000K
Lumen Output	2200lm
Light Efficiency	73,33lm/W
CRI	80
Beam Angle	38°
Illumination Diagram	
Packing Info	
Box Length	18cm
Box Width	18cm
Box Height	
Box Holgin	11cm
Box Weight	11cm

 Pcs/Carton
 18

 Barcode
 5291889042266

 HS Code
 9405409900

Energy Label



Certification & Warranty

Warranty 2 Years
Weee Directive Yes

switch to one light!

