



Product Datasheet

08 Downlights Adjustable LED>The COB Shop Downlights Pro

11150A/W/C



50W COB LED Recessed adjustable downlight, shop range, IP20.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



Gallery




Physical Specification

Product Type	Gear
Item Group	08 Downlights Adjustable LED
Family	The COB Shop Downlights Pro
Order Code	11150A/W/C
Colour	White
Material	Die Cast
Shape	Circular

Height	135mm
Diameter	184mm
Cutout Hole Diameter	165mm
Recessed Ceiling	Yes
Depth Required	160mm
Indoor	Yes
Adjustable	2 Directions
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	50W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	1200mA
Voltage	40V
Safety Class	
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ

LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	32,4-50,4W
Power Factor	0,9
Constant Current	Yes
1200mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Illumination Data	
Illumination Data Colour Temperature	4000K
	4000K 4450lm
Colour Temperature	
Colour Temperature Lumen Output	4450lm
Colour Temperature Lumen Output Light Efficiency	4450lm 89lm/W
Colour Temperature Lumen Output Light Efficiency CRI	4450lm 89lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4450lm 89lm/W 80 40°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4450lm 89lm/W 80 40°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	4450lm 89lm/W 80 40°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4450lm 89lm/W 80 40°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	4450lm 89lm/W 80 40°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length	4450lm 89lm/W 80 40° \$\int_{\text{1}} = \text{25cm}
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width	4450lm 89lm/W 80 40° 25cm 20cm
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Box Length Box Width Box Height	4450lm 89lm/W 80 40° 25cm 20cm 16cm

Energy Label



Certification & Warranty

Warranty 2 Years

Wee Directive Yes

switch to one light!

