

14 Wall & Ceiling LED > The COB Indoor Round Cylinders

12104M/W



4,5W COB LED cement with black reflector, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Physical Specification

Item Group	14 Wall & Ceiling LED
Family	The COB Indoor Round Cylinders
Order Code	12104M/W
Colour	White
Material	Cement
Shape	Circular
Height	110mm

Diameter	75mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
------	----------

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	4,5W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting


Input Type	Constant Current
Input Current	350mA
Voltage	8,6V
Power(Watts)	3W
IP Rating	IP20
Light Source	LED built in
LED Brand	Bridgelux

Gear

Gear Type	Led Driver
Input Voltage	100-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	2,1-4,2W
Power Factor	0,95
Constant Current	Yes
350mA	6-12V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	350lm
Light Efficiency	77,78lm/W
CRI	90
Beam Angle	40°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	13cm
Box Width	13cm
Box Height	16,5cm
Pcs/Carton	18
Barcode	5291889056096
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

