

2010-2-PIB-80

Addressable Fire Panel Accessory - Peripherals Interface Board 8 Outputs

Overview

The 2010-2-PIB-80 Peripherals Interface Board is an accessory of the small to medium size intelligent addressable life safety control systems. In total there are 4 variants of this board. The 2010-2-PIB-80 is a reduced variant of the 2010-2-PIB and is perfect if your only looking for having additional supervised outputs to interface other electronic equipment on site.

Functionality

The 2010-2-PIB-80 Peripherals Interface Board provides eight outputs for compatible control panels. The board can be powered from the control panel or from an external power supply, providing 24 VDC to each of the supervised outputs. Outputs are supervised for short circuit and open circuit faults.

Mounting & Connections

The board can be plugged directly on the front of the main board inside the big size control panel variants on top of the new release 3 chassis. No additional wiring is required. You can use the pluggable connectors to make your connections to the field wiring. Connect an external power supply to the board directly to reduce the load of your system.



Details

- 8 supervised outputs
- Option to externally power
- Pluggable connectors

2010-2-PIB-80

Addressable Fire Panel Accessory - Peripherals Interface Board 8 Outputs

Technical specifications

Electrical

Power supply type	VDC
Operating voltage	24 VDC

Physical

Physical dimensions	105 x 192 mm (W x H)
Net weight	126 g
Shipping weight	220 g
Mounting type	In cabinet

Environmental

Operating temperature	+5 to +40°C
Storage temperature	-20 to +50°C
Relative humidity	10 to 95% noncondensing

Standards & regulation

Certification	EN54-2, EN54-13
Standards	EN54-2, EN54-13
Environmental	CPD, WEEE, RoHS

Operating voltage

24 VDC

Current supply

Standby	40 mA max.
Activated	4050 mA max.

Current per output

Activated	500 mA at 25°C
-----------	----------------

End-of-line termination

Output (typical)	EOL 15 kOhm, 1/4 W resistor
Output (EN 54-13)	EOL Class B (EN 54-13) device

Operating environment

Operating temperature	-5 to +40°C
Storage temperature	-20 to +50°C
Relative humidity	10 to 95% (noncondensing)

Weight

126 g

Dimensions (W x H)

105 x 192 mm

Compatibility

Release 3 hardware / firmware

