

MINI AUDIO WITH HANDSET





2738W/A

SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET





Mini series door-entry phone with handset for Simplebus 2 audio systems. Equipped with a key button, button for additional services such as calls to the porter switchboard..., call volume adjustment, Silent mode (Privacy) and floor call input. Correct positioning of the handset on the base is facilitated by invisible magnetised panels. The additional board art. 2735 is available to purchase separately, for an additional button with voltage free contacts and call repetition. Fitted with terminal art. 1214/2C.

AWARDS

DESIGN



MINI AUDIO WITH HANDSET





2738W/A

SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET

	GENERAL DATA
Height (mm)	190
Depth (mm)	28
Type of finishing materials	ABS
Product weight (g)	300
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes

AUDIO FEATURES	
Microphone	9.6 (ø) x 6.9mm, omnidirectional
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W
Technologies implemented	Full-Duplex

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Supply voltage	22÷35VDC
Maximum absorption (W)	0.8

HARDWARE FEATURES	
Type of buttons	Mechanical
Service buttons	Lock-release
Clamps	L L CFP CFP

The technical specifications are subject to change without prior notice.



MINI AUDIO WITH HANDSET



2738W/A

SIMPLEBUS2 MINI DOOR ENTRY PHONE WITH HANDSET	
HARDWARE FEATURES	
Number of inputs (n°)	1
SETTINGS	
Ringtone volume	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES	
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 90
Environmental class	Ш
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES	
Door opener	Yes
Absorption during call (mA)	25
Absorption during communication (mA)	20
Maximum current absorption (mA)	25
Minimum current absorption (mA)	1
CPS call	Yes
Actuator control	Yes
Outside door call input	Yes
Silent mode (Privacy)	Yes