



IKALL

1/2



3332

IKALL SERIES AUDIO INDUCTION LOOP MODULE



Ikall series module with audio induction loop which allows hard-of-hearing users to listen to the audio conversation on the external unit via their own hearing aid device (with T switch). Module for use in conjunction with the 2-wire audio/video unit art. 4681BM or the ViP audio/video module art. 4682BM. Dimensions: 112x89.5x38 mm

COMELIT

VIDEO DOOR ENTRY SYSTEMS & KITS

IKALL

2/2



3332

IKALL SERIES AUDIO INDUCTION LOOP MODULE		
	GENERAL DATA	
Height (mm)	89.5	
Width (mm)	112	
Depth (mm)	38	

COMPATIBLE SYSTEMS		
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes	
Audio Simplebus 2 with power supply art. 1210/1210A	Yes	
Audio Simplebus 1	Yes	
ViP	Yes	

ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Absorption in stand-by (W)	15

ENVIRONMENTAL AND COMPLIANCE FEATURES		
Operating temperature (°C)	-25 ÷ 55	
Operating humidity (RH max) (%)	25 ÷ 95	
Environmental class	IV	
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011)	