

EXprox²K



Proximity Readers

EXprox²K is a range of high-performance contactless proximity readers from TDSi.

EXprox²K is designed to be mounted in a standard electrical back-box making for a neat and simple installation. All products are supplied with a choice of covers allowing the look of the reader to be changed to suit its surroundings.

SPECIFICATIONS

TDSi Part No.	5002-0396
Dimensions	102 x 102 x 20 mm. Connector including terminal block protrudes by 11 mm from rear face.
Weight	270 g
Operating Environment	-20°C to +55°C, 0 to 95 %RH (non-condensing)
Power Supply	9 to 16 VDC, 75 mA max
Operating frequency	126 kHz (nominal)
Card technology	EM4100, EM4102, EM4200 and compatible
Sounder	Integral with external control
LEDs	2 - red and green both with independent external control. Bi-colour input capability for connection to TDSi access control units.
Read range	150 mm (nominal) with ISO card, 70 mm (nominal) with tag
Output formats	Mag stripe, 26-bit Wiegand

ORDERING INFORMATION

Part Number: 5002-0396


Description: EXprox²K proximity reader with keypad

Part Number: 4262-0245

Description: ISO white proximity card

Part Number: 4262-0246

Description: Proximity tag



FEATURES & BENEFITS

Mounting into a standard electrical back-box

Neat installation into a standard fitting.

Tough plastic clip-on covers in both graphite and light grey

Adapt the look of the reader to suit the surroundings.

Supports the 2 Reader Mode of MICROgarde access control units

Use MICROgarde to control 2 doors both with read-in/read-out. Saves on hardware, installation time and cost.

Available with a blue backlit keypad

Increase security by adding a PIN to your card-based access control.

Pluggable terminal block cable termination

Allows the cable to be pre-wired prior to installation of the reader for convenience.

Fully encapsulated design

Provides maximum protection against water ingress making it suitable for mounting both indoor and out.

Integral LEDs and sounder

Gives the user unambiguous audible and visual indication of card reads and access status. Maximises user confidence.

Industry standard outputs

Allows connection to all standard access control panels.

Read range of 150 mm (nominal)

Easy to use.



TDSi UK
Unit 10 Concept Park,
Innovation Close,
Poole,
Dorset BH12 4QT
United Kingdom
t: +44 (0)1202 723535
f: +44 (0)1202 724975
e: sales@tdsi.co.uk

TDSi France
Immeuble ATRIA,
2 rue du Centre
93160 NOISY LE GRAND,
France
t: +33 (0)1 58 84 20 90
f: +33 (0)1 58 84 20 91
e: infos@tdsi-france.com

TDSi China
Rm 103, 1 Bid,
Shangsha Innovation Science
& Technology Park,
9283 Binhai Road,
Futian District,
Shenzhen 518048,
P.R.China
t: 86-755-82535725,
82535720
f: 86-755-82535770
e: tdsiinfo@microgarde.com.cn