

PANELgarde



PANELgarde

PANELgarde from TDSi is a versatile reader for door entry panels with a square or circular cut-out offering a wide range of output formats.

Fully encapsulated, PANELgarde is suited for the harsh environments such as high RH/condensation and extremes of temperature that can be experienced inside a door entry panel. Positive audible and visible indication is provided by an integral sounder and bi-coloured LED, which is controllable externally.

PANELgarde

SPECIFICATIONS

TDSi Part No.	5002-0430
Dimensions	73 x 73 x 12 mm
Weight	90g
Operating Environment	-10 °C to +50 °C, 0 to 95 %RH (non-condensing)
Power supply	10 to 14 VDC, 150 mA max
Operating frequency	125KHz
Card technology	EM4102 Compatible
Sounder	Integral
LEDs	1 bi-colour (red/green) with independent external control
Read range	<80 mm with ISO card, <30 mm with tag
Output formats	Mag stripe, 26-bit wiegand
Fixings	48mm centres

ORDERING INFORMATION

Part Number: 5002-0430 Description: Panel mount reader

Part Number: 4262-0245

Description: EM4100 ISO Proximity Card

FEATURES & BENEFITS

Uses 125 KHz EM410x technology

Uses standard cards—no tie-in to any particular manufacturer.

Panel mounting holes

Mounts in standard door entry panels with square or round cut-outs to give a neat integrated solution.

Simple to install

Minimises installation time and cost.

Fully encapsulated design for maximum

liquid and dust ingress protection Waterproof design allows reader to be mounted both inside and out.

Wide range of output formats including clock and data, Wiegand

Compatible with all standard access control panels. Can also be used in other applications.

Integral sounder and bi-coloured LED with external control

Unambiguous audible and visual indication of card reads and access status. Maximises user confidence.





TDSi UK Unit 10 Concept Park, Innovation Close, Poole, Dorset BH12 4QT United Kingdom t: +44 (0)1202 723535 f: +44 (0)1202 724975 e: sales@tdsi.co.uk

TDSi France Immeuble ATRIA, 2 rue du Centre 93160 NOISY LE GRAND, France t: +33 (0)1 58 84 20 90 f: +33 (0)1 58 84 20 91 e: infos@tdsi-france.com TDSi China Rm 103, 1 Bld, Shangsha Innovation Science & Technology Park, 9283 Binhai Road, Futian District, Shenzhen 518048, P.R.China t: 86-755-82535725, 82535720 f: 86-755-82535770 e: tdsiinfo@microgarde.com.cn

This datasheet is not intended to form any part of a contract. TDSi reserves the right to change the specification or appearance of any of its products.