

MIFARE Mullion Readers

5002-0610, 5002-0620, 5002-0630

Stylish and fully featured MIFARE® readers from TDSi.

A stylish and full featured range of mullion readers from TDSi featuring MIFARE technologies.

TDSi is pleased to offer high quality mullion readers in robust polycarbonate housings with excellent read range.



Features and Benefits.

Compatible with ISO 14443-A standard for 13.56MHz

One card for all applications including cashless vending.

Fully encapsulated design

Provides maximum protection against water ingress making it suitable for mounting both indoor and out.

Integral LEDs

Provides clear visual indication of access status.

In-built sounder

Gives unambiguous feedback of card reads.

Choice of output options

Allows connection to the majority of access control systems.

Multiple mounting options

Able to be mounted to a single gang electrical box or directly to a non metallic surface.

Dimensions



Part No.	5002-0610, 5002-0620, 5002-0630
Dimension	45 x 130 x 17mm
Weight	250g
Operating Environment	-20°C to +55°C, 0 to 95% RH (non-condensing)
Power Supply	7 to 14VDC, 200mA (Max)
Operating Frequency	13.56MHz (nominal)
Card Technology	ISO14443A; MIFARE Plus, DESfire, Classic
Sounder	Integral
LED's	RGB
Read Range*	<50mm
Output Formats	Magnetic Stripe, Wiegand 26-bit** / 34-bit / 37-bit

Ordering Information

Part Number: 5002-0610

Description: TDSi MIFARE Serial Reader

Part Number: 5002-0620

Description: TDSi MIFARE Sector and PLUS Reader

Part Number: 5002-0630

Description: MIFARE Plus and DESfire Reader

*Figures may vary between cards and installation

**As standard. Contact TDSi for alternative configurations