

## MARINE VIDEO PANEL VDS DIGITAL ST3



### Reference: 5468

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc.  
Incorporates COLOUR camera with built-in lighting and pan&tilt regulation system...

## DESCRIPTION

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc.  
Incorporates COLOUR camera with built-in lighting and pan&tilt regulation system to adjust the camera lens.

Fermax Marine Line ..... in stainless steel.

Marine is the anti-vandal panel line manufactured in 2.5 mm thick stainless steel.. Straight lines that highlight the quality of the steel. State of the art technology and resistance to even the most corrosive, humid and dangerous atmospheres.

Colour aluminium

Dialling keypad.

Backlit LCD 2 line display, 16 characters each.

### VDS system:

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video). Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).



Maximum distance from first access to last home: 200 m.

## TECHNICAL SPECIFICATIONS

IP54 IK09

Video

- Resolution: 500 lines.
- Sensor: 1/3" color CMOS.
- Effective pixels: 469K
- Minimum external illumination: 1 lux.
- SNR >45dB.
- Frame rate 25 fps.
- Auto iris.
- Auto BLC.
- View angle 68° H, 51°V.
- Color night vision through white led.

Series ST3 Panel.

- Panel measurements: 150x360 mm (width-height):
- Flush-fit box dimensions: 130x340x55 mm (height-width-depth).
- Surface mounted box dimensions: 154x364x95 mm (height-width-depth).

Hood: 154x364x40 mm (height-width-depth).

Power supply: 18 Vdc

The house call is made by entering the corresponding code assigned to the home + the "bell" key.

Electronic directory: lets you look for the names (home owners/residents) through the display and browser buttons.

Access Control: incorporates access control functions through the numeric keypad by means of keypad codes (programmed previously).

Consumption:- Standby: 100 mA- Active audio: 200 mA- Lighting per lamp: 70 mA

Audio capacity home-outdoor panel: 2W

Audio capacity outdoor panel-home: 0.15W

Two-way volume control

Operating temperature: -10 to 60 °C

**Weight:** 3,3130224 kg

**Size of product when packed:** 37x16,4x8,2 cm

**EAN 13:** 8,4243E+12