

## AUDIO VDS DIRECT CITY PANEL



**Reference:** 7308

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc.

### DESCRIPTION

Installed in the accesses to the building, they enable communication with homes, door opening, guard unit call , etc.

New Cityline Panel:

CityLine is the "continuous profile" outdoor panel line for buildings.

This new panel model is more robust, more luxurious and higher design and functional quality. The new design, in its video entry version, includes audio and video functions in the same module.

Colour aluminium

Dialling keypad.

**VDS system:**

Simplified installation audio and video door entry system that does not use house call wires. The call is made by transmission of a digital call code generated by the VDS amplifier.

- In new works, installation can be carried out with the following type of wiring: UTP CAT5 / 5 wire / 3 wire + Coaxial (video). Lets you manage up to 199 homes, 2 entrance accesses and a central guard unit.

Maximum distance from first access to last home: 200 m.

- In replacement works, the change from analogue entry to video entry system can be done taking advantage of the existing wiring.

The system capacity and distance will depend on the installation wiring.

VDS amplifier comes with voice synthesizer as standard issue.

When the door release is activated a message is heard: "The door is open, please close the door behind you".

The home terminals require simple programming done from the outdoor panel. By means of this programming a call code is assigned to each terminal (telephone or monitor).

Communication is private.

Wiring. Audio: 3-wire bus. Video: UTP CAT5 / 5 wire / 3 wire + Coaxial (video).

Maximum distance from first access to last home: 200 m.



## TECHNICAL SPECIFICATIONS

Series 5 Panel.

- Panel measurements: 130x246 mm (width-height):
- Flush-fit box dimensions: 115x233x45 mm (height-width-depth).
- Surface mounted box dimensions: 130x246x33 mm (height-width-depth).

Power supply: 18 Vdc

The house call is made by entering the corresponding code assigned to the home + the "bell" key.

Access Control: incorporates access control functions through the numeric keypad by means of keypad codes (programmed previously).

Consumption:

- in standby: 52 mA.
- call: 182 mA.
- active audio: 312 mA.
- audio+video: 392 mA (camera consumption: 80mA)

Audio capacity home-outdoor panel: 2W

Audio capacity outdoor panel-home: 0.15W

Two-way volume control

Operating temperature: -10 to 60 °C

**Weight:** 1,0128034 kg

**Size of product when packed:** 26,5x13,8x7 cm

**EAN 13:** 8424299073088