Product data sheet



AB301

Mid power beacon - amber lens

The range of low and high profile XENON beacons offers maximum light output and high efficiency for use in 10-15 V intruder alarms. Tested for IP65 rating, with polycarbonate lenses as standard, they are suitable for the most demanding applications.



Details

- Maximum light output
- High efficiency
- Tested to IP65 rating
- Polycarbonate lens

AB301

Mid power beacon - amber lens

Technical specifications

General	
Accessory group	Beacon
Туре	Accessory
Electrical	
Operating voltage	12 V
Power consumption	1 W
Current consumption	115 mA
Physical	
Physical dimensions	75 x 51 mm
Environmental	
Operating temperature	-30 to 70°C
IP rating	IP65
Power supply	
	10 to 15 VDC
Current consumption	
	115 mA
Power output	
	1 W
Flash energy	
	0.9 nominal J
Flash frequency	
	60 flashes/min
Electrical connections	
	2 leads
Installation	
	Mounting base included
Base colour	
	White
Lens colour	
	Amber
Dimensions (Ø x H)	
	75 x 51 mm
Operating temperature	
	-30 to +70°C

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

