### **Product data sheet**



# ACL760

## Vandal proof standalone keypad slim housing

### Standalone vandal-proof keypad

Mullion and vandal-resistant access control keypad with metal keys for doorframe mounting. With user memory of 99 codes and one push button, ACL760 is the best solution for single door access control. Photoelectric sensor for automatic illumination is effective in low-lit conditions. ACL760 with a rugged good look is designed to operate even in harsh environments.



#### **Details**

- Indoor/outdoor
- Dust proof and water-resistant
- Up to 99 user codes
- Up to 3 peripherals (keypad/proximity reader) can be connected
- Codes can be 1 to 8 digit long

# ACL760

# Vandal proof standalone keypad slim housing

# **Technical specifications**

General	
User interface	Touch Buttons
Communication	
Communication type	Wired
Electrical	
Operating voltage	12/24 VAC/DC
Power supply type	VAC
Current consumption	70 mA max
Physical	
Form factor	Vertical
Mounting type	Surface Mount
Environmental	
Operating temperature	-25 to 60 °C
Relative humidity	0 to 95% non-condensing
Supply voltage	
	12/24 VAC/DC
Current consumpti	ion
	70 mA max
Outputs	
Relays	1 relay and 1 transistors
Operating temperature	
	-25 °C to +70 °C
Operating humidity	
	0 to 95% (non-condensing)
Cabel	
	3 m

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

