

ACL800-PB-B

ACL800 Request-To-Exit Touch capacitive push button - Stand alone, Surface mount, Black

Product description

ACL800-PB Series is a Request-To-Exit Surface mount Push Button switch, it will work independently (standalone) or can equally be connected via a controller to provide exit from a secured area (Push Button Input). It includes a buzzer and a dual LED. The ACL800-PB Series can work in pulse (3, 5, 10 sec) or latch mode.

The ACL800 range

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.



Details

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Touch Sensitive Technology
- Includes a buzzer
- Dual LED
- Work in pulse (3, 5, 10 sec) or On/Off latched mode
- Surface mount
- Backlight illumination
- Request-To-Exit Touch capacitive push button

ACL800-PB-B

ACL800 Request-To-Exit Touch capacitive push button - Stand alone, Surface mount, Black

Technical specifications

Technology

Request to Exit	Touch Sensitive
-----------------	-----------------

System

RTE (Request To Exit)	Yes
-----------------------	-----

No. of LEDs	2
-------------	---

Interface & connections

Connector type	Pigtail
----------------	---------

Pigtail length	100 cm
----------------	--------

Exit	Relay 1A (NO/C/NC)
------	--------------------

Relay Output	On/off Latched or Timed (3, 5 or 10 seconds)
--------------	--

Tamper type

Pry-off tamper	No
----------------	----

Opening tamper	Yes
----------------	-----

Operation

Stand-alone	Yes
-------------	-----

Backlighting	Green (Door opened) - Red (Door Closed, Denied, Blocked) - Orange (Idle)
--------------	--

Visual and Sound signals	Complete button lighting + buzzer
--------------------------	-----------------------------------

Support

Language installation manual	English
------------------------------	---------

Electrical

Power supply type	VDC
-------------------	-----

Power supply value	5 to 24 VDC 15 to 24 VAC
--------------------	-----------------------------

Current consumption	Typical 45 mA at 24 VDC Maximum 65 mA at 24 VDC Typical 65 mA at 12 VDC
---------------------	---

Physical

Physical dimensions	92 x 51 x 27 mm
---------------------	-----------------

Net weight	163 g
------------	-------

Shipping weight	295 g
-----------------	-------

Colour	Black
--------	-------

Material	ABS
----------	-----

Form factor	Mullion
-------------	---------

Mounting type	Surface Mount
---------------	---------------

Environmental

Operating temperature	-20 to +50°C
-----------------------	--------------

Storage temperature	-20 to +50°C
---------------------	--------------

Environment	Indoor / Outdoor
-------------	------------------

Standards & regulation

Compliance	CE, RoHS
------------	----------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

15 April 2019 - 15:06



**United
Technologies**

Climate | Controls | Security