

# AS526

## Self-activating outdoor siren with dual red beacon

---

The AS520 Series comprises a range of quality designed sirens that meet today's security and environmental residential requirements. With its attractive housing, the choice of lens colours and the possibility to mount horizontally or vertically the siren can easily fit any place. The housing in UV-proof and high impact resistant, 3-mm polycarbonate and an optional inner cover provide the ultimate protection.



### Details

---

- Attractive high quality shaped housing
- Double piezo sounder with 114 dB @ 1m sound output
- Vertical or horizontal mounting
- Fully potted electronics
- On-board Ni-Cd-battery
- Double strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Self detection of cable cutting or tampering
- Hold-off polarity selection
- Independent hold-off for both beacon and siren
- A choice of cut off time

# AS526

## Self-activating outdoor siren with dual red beacon

### Technical specifications

---

#### General

Accessory group	Siren
Type	Outdoor siren

#### Material

Material	Polycarbonate (3 mm)
----------	----------------------

#### Sounder

Sounder	Double piezo
---------	--------------

#### PCB protection

PCB protection	Fully potted
----------------	--------------

#### Tamper & pry-off

Tamper & pry-off	Yes
------------------	-----

#### Power supply

Power supply	10.0 to 14.5 VDC
--------------	------------------

#### Standby current (typical)

Standby current (typical)	40 mA (with NiCd battery)
	20 mA (without battery)

#### Operating current (typical)

Operating current (typical)	350 mA
-----------------------------	--------

#### Sound output

Sound output	114 dB
--------------	--------

#### Frequency

Frequency	0.5 to 3 kHz
-----------	--------------

#### Operating temperature

Operating temperature	-25 to +55°C
-----------------------	--------------

#### Flash frequency

Flash frequency	50 to 60 flashes/min
-----------------	----------------------

#### Cut-off timer

Cut-off timer	3 min, 5 min, 10 min, 20 min
---------------	------------------------------

#### Self-activating battery

Self-activating battery	10.8 V / 280 mAh
-------------------------	------------------

#### Comfort LED

Comfort LED	Yes
-------------	-----

#### Dimensions (W x H x D)

Dimensions (W x H x D)	210 x 300 x 55 mm
------------------------	-------------------

#### Low voltage detection

Low voltage detection	Yes
-----------------------	-----

#### Metal inner cover

Metal inner cover	Optional
-------------------	----------

#### Lead acid battery

Lead acid battery	Optional
-------------------	----------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

25 February 2019 - 17:40



**United  
Technologies**

Climate | Controls | Security