

AS700

Outdoor hardwired siren - NFa2P & EN50131-4 approved

Overview

The sounder provides a maximum sound output of 112 dBA and offers a host of features including silent engineer start-up, front & rear tamper, low current consumption, diagnostic fault LED, Ring Line monitoring and a battery test feature (with fault output).

The electronics modules are conformal coated to provide additional protection from harsh environments thus ensuring a long working life.

Certified to the latest European standards

The sounder fully meets and is certified to the requirements of EN50131-4:2009 Grade 3, supporting the new functional and operational features now required.

The external sounder is an NFa2P certified device designed for intruder alarm systems.



Details

- Certified to NFa2P (Type 3) & to EN50131-4:2009 Grade 3, Environmental class IV
- Long working life
- Easy installation and maintenance
- Low current consumption, standby and alarm
- Replaceable internal battery
- Selectable cut-off timer, Silent Engineer start-up mode
- 3 year warranty

AS700

Outdoor hardwired siren - NFa2P & EN50131-4 approved

Technical specifications

General

Accessory group	Siren
Type	Outdoor siren

Electrical

Operating voltage	9 to 15Vdc
-------------------	------------

Physical

Physical dimensions	350x200x75
Net weight	1.1Kg
Colour	White
Material	ABS

Environmental

Vandal proof	Yes
Environment	Outdoor

Standards & regulation

Compliance	CE
Certification	CE, EN50131 Grade 2, NFA2P

