

AT Transom Housings

New versions added to our range

Range: Magnetic Locking

A new range of transom housings have been introduced to the CDVI range. Available for single or double doors, and for use with 300kg or 500kg magnets.

Transom housings provide a smarter finish to the installation of magnetic locks, and form part of the door frame. Transoms provide a secure fixing for magnets which is ideal for use in public buildings where safety is paramount. For use on inward opening doors, the transom housing will be fixed to the header above the door, and Z brackets will be required to install the armature on the door leaf.

Vertical fix transoms are also available, for fixing magnets to the leading edge of the door frame vertically - if this option is required, then the BO600RP and/or BO800RN should be considered as an alternative.



AT300 variations



AT500-2-2H + AT500M(2)



C3M11/M3000



AT500M



300/500Z for inward opening doors

Product codes

AT300-1H	1m housing, 1cut out for C3M11/M300M- 1000 x 50 x 37 mm
AT300-2-1H	2m housing, 1 cut out for C3M11/M300M - 2000 x 50 x 37 mm
AT300-2-2H	2m housing, 2 cut outs for C3M11/M300M - 2000 x 50 x 37 mm
AT300-2-2HV	2m vertical housing, 2 cut outs for C3M11/M300M - 2000 x 50 x 37 mm
AT300-1L	L bracket for AT300-1 metre housing - 1002(L) x 38 x 38 mm
AT300-2L	L bracket for AT300-2 metre housing - 2002(L) x 38 x 38 mm
AT500-1H	1 metre housing, 1 cut out for AT500M - 1000 x 70 x 50mm
AT500-2-1H	2 metre housing, 1 cut out for AT500M - 1998 x 70 x 50mm
AT500-2-2H	2 metre housing, 2 cut outs for AT500M - 1998 x 70 x 50mm
AT500-2-2HV	2 metre vertical housing, 2 cut outs for AT500M - 1998 x 70 x 50mm
AT500-1L	L bracket for AT500-1 metre housing - 1000(L) x 50 x 50mm
AT500-2L	L bracket for AT500-2 metre housing - 1998 (L) x 50 x 50mm
AT500M	Monitored 500kg magnet for AT500 housings - 228 x 39 x 27mm 12/24Vdc, 500mA, COM/NO/NC