

ATS1455

(10 PACK) Secure ATS PVC Card

Product overview

The ISO card in white color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV2 encryption. It can be used in secure mode with ATS118x range readers and ATS1136 keypad.

When used on other Mifare Readers the standard Mifare 7-byte CSN is provided instead of the secure card data.



Details

- Attractive designed keyfob in ISO card model
- Card data secured by AES encryption
- Mifare Desfire EV2 encrypted application

ATS1455

(10 PACK) Secure ATS PVC Card

Technical specifications

Technology

| | |
|--------------------------------|--|
| Credential type | Smart card |
| Credential operating frequency | 13.56 MHz |
| Supported technology 13.56 MHz | Mifare DESFire EV2 (CSN), MIFARE DESFire EV2 (UTC) |

System

| | |
|-------------------|---|
| Reading distance | Secure mode: between 1 - 5 cm Unsecure mode: between 2-5 cm Distance may vary based on reader |
| Custom data model | No |
| Memory size | 2K |
| Supported readers | ATS ATS118x Secure Readers |

Printing

| | |
|-------------------------|----|
| Direct surface printing | No |
|-------------------------|----|

Ordering information

| | |
|------------------------|----|
| Minimum order quantity | 1 |
| Cards/tags in package | 10 |

Physical

| | |
|---------------------|----------------|
| Material | PVC |
| Form factor | Clamshell |
| Physical dimensions | 86 x 54 x 9 mm |
| Net weight | 66 g |
| Shipping weight | 67 |
| Colour | White |
| Card Label | Serial number |

Environmental

| | |
|-----------------------|--------------|
| Operating temperature | -10 to +50°C |
| IP rating | IP68 |

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.