Product data sheet



ATS1500A-IP-MM-RK

Kit ATS1500A-IP-MM including ATS1115A keypad



Details

- 8 onboard zone inputs
- Max 32 zones: wired, wireless or mixed
- Economic input and output plug-in expansion
- Up to 16 shock sensor inputs
- 4 areas
- Up to 50 users
- EN50131 Grade 3 (when ATS-MM-TK added) / Environmental class 2
- USB port for local configuration
- Plug-on PSTN dialler for reporting or configuration
- Multilingual: language configurable per user
- Integrated 10/100Mb Ethernet connection
- IP alarm reporting to OH-NETREC receiver Optional GPRS
- Integrated access control & support for ATS125x door controller

ATS1500A-IP-MM-RK

Kit ATS1500A-IP-MM including ATS1115A keypad

Technical specifications

System			
Product type	Integrated Access Control		
Panel type			
No. of keypads / readers	Hybrid		
	15		
Data Gathering Panels (DGP)	13		
No. of alarm groups	16		
Specified cable	WCAT52, WCAT54		
Inputs			
Max no. of inputs	32		
Onboard inputs	8		
Inputs plug-in expansion	1 8		
Outputs			
No. of outputs	128		
No. of onboard outputs	5		
_			
Area			
No. of areas	4		
User/Cards			
Max. no. of users	50		
Max. no. of cards	50		
Max. no. of PIN codes	50		
Access control			
Standard doors on	4		
control panel			
Door groups	128		
Intelligent doors on 4-door DGPs	28		
Communication			
Onboard transmission	IP		
type			
Transmission extension	GSM/GPRS, PSTN		
Databus type	RS485		
Event log			
Alarm event log	250-1000		
Access event log	10000		
Electrical			
Power supply type	230 VAC		
Power supply value	230 VAC +10%, -15%, 50 Hz		
Mainboard current	150 mA		
consumption			
Max system current	950 mA at 13.8 V ±0.2 V		
Max aux power current	840 mA		
Auto-reset fuses	5		
Glass break fuses	1		
Physical			
Physical dimensions	315 × 388 × 85 mm		
Housing	Medium Metal		

Environmental

Operating temperature	-10 to +55°C	
Relative humidity	95% (non-condensing)	
Environmental Class	Class II, indoor	
IP rating	30	

Standards & regulation		
EN50131 Grade	Grade 3	
Compliancy	CE	

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

