

## BF370S

Manual 'No Break' Call Point surface



### Overview

Certified to EN54 Parts 11 (LPCB) and 13 (BSI).

Smooth-action resettable element mimics the feel of breaking glass.

Supplied with a red back box, reset key and 'Not in Use' label.

Red LED 'alarm ring' illuminates call point face upon activation.

Photoluminescent operating window remains visible for up to 5 minutes.

Flush version (order code BF370SF) without a red back box also available (note a BF370SFP flush mounting plate is also required for flush mounting - see spares & accessories section below for further details).

### Technical Specifications

<b>Approvals/certifications</b>	Certified to EN54 Parts 11 by the LPCB and 13 by the BSI.
<b>Supply/operating voltage</b>	4.5-30Vdc
<b>Product dimensions (mm)</b>	87 W x 88 H x D 62mm (includes back box).
<b>Construction &amp; finish</b>	Red ABS.



<b>IP Rating</b>	IP42.
<b>Weight</b>	TBC.
<b>Properties</b>	Supplied with a 470 $\Omega$ & 680 $\Omega$ resistor (value selected by wiring connection).
<b>Operating conditions/temperature</b>	-30°C to +70°C.



T 01942 322744    E sales@c-tec.co.uk  
F 01942 829867    W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744 E [sales@c-tec.co.uk](mailto:sales@c-tec.co.uk)  
F 01942 829867 W [www.c-tec.com](http://www.c-tec.com)



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom