



# BS129N

Battery 12 V 26 Ah



## Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

# BS129N

## Battery 12 V 26 Ah

### Technical specifications

---

#### Electrical Characteristics

---

Nominal voltage	12 V
Nominal capacity	above 20 Ah
Internal approx. resistance	10 mOhm

---

#### Charge / discharge

---

Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	7.8 A
Max. discharge current	130 A

---

#### Temperature

---

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

---

#### General

---

Product type	Sealed lead acid battery
--------------	--------------------------

---

#### Physical

---

Physical dimensions	166 x 175 x 125 mm
Net weight	9.528 kg
Shipping weight	9.528 kg
Material	ABS
Terminal type	MS bolt & nuts

---

#### Environmental

---

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

---

#### Standards & regulation

---

Compliance	CE, RoHS 2, WEEE
Certification	VdS

---

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

25 February 2019 - 9:13



**United  
Technologies**

Climate | Controls | Security