



BS133N

Battery 12 V 65 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS133N

Battery 12 V 65 Ah

Technical specifications

Electrical Characteristics

Nominal voltage	12 V
Nominal capacity	above 20 Ah
Internal approx. resistance	10 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC @ +20°C
Max. charge current	19.5A
Max. discharge current	325 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

General

Product type	Sealed lead acid battery
--------------	--------------------------

Physical

Physical dimensions	350 x 166 x 174 mm
Net weight	23.0 kg
Shipping weight	23.0 kg
Material	ABS
Terminal type	MS bolt & nuts

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Standards & regulation

Compliance	CE, RoHS 2, WEEE
Certification	VdS

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

6 March 2019 - 8:35