



CA5100A

1-BUTTON CIAO ENTRANCE PANEL. 4+N



Ciao Series modular entrance panel with synthetic polymer front cover offering resistance to atmospheric agents (protection rating IP54 and coating with anti-UV treatment) and acts of vandalism (protection rating IK08); blue LED nameplate backlighting. Complete with call button art. CA9213. Supplied with a surface-mount installation support. Traditional 5-wire system.



CA5100A

1-BUTTON CIAO ENTRANCE PANEL. 4+N

GENERAL DATA

Type	Monoblock
Height (mm)	172
Width (mm)	100
Depth (mm)	28
Product color	Grey RAL 9006
Product weight (g)	400
Type of finishing materials	Polymeric
Wall-mounted	Yes

COMPATIBLE SYSTEMS

Traditional	Yes
-------------	-----

AUDIO FEATURES

Microphone	4mm (Ø), Omnidirectional
Loudspeaker	50mm (Ø), 50 Ohm, 0.25W

ELECTRICAL CHARACTERISTICS

Type of power supply	External power supply
Supply voltage	12VAC
Absorption in stand-by (W)	1.3
Maximum absorption (W)	12.5

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Backlight colour	Blue
Removable terminals	Yes

SETTINGS



CA5100A

1-BUTTON CIAO ENTRANCE PANEL. 4+N

Loudspeaker volume	Yes
Microphone volume	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
-------------	-----