

## CDV97-ID

The CDV97 range of Door Stations features a colour 2 mega pixel CMOS camera with a 170 degree viewing angle with digital pan, tilt and zoom using the CDV47MG-V2 monitor.

The CDV97 range also includes a built in proximity reader programmable to operate internally via the internal lock relay or externally via CDV-ACC BUS/Wiegand interface allowing direct connection to a standard wiegand reader input port. The CDV97 is available in 1, 2 and 4 user variants.

The modern low profile styling suits all environments and is compatible with all of the 2Easy range.



The 2EASY system from CDVI offer convenient and high quality video entry. Connection throughout is 2-wire, non polarised providing simple and efficient installation and maintenance.



CDV97-1ID



CDV97-2ID



CDV97-4ID



CDV17-97A

## CDV97-ID - Technical Specifications

### Product Specifications

Material: Zinc allow panel  
Surface wall-mount / flush mount  
IP Rating: IP54

### Camera

Colour CMOS, 2.0 Mega pixel  
1/2.7" fisheye sensor, 170° wide angle

### Output Specifications

Number of realy circuits: 2\*  
\*the second lock output requires CDV-RLC

### Electrical Specifications

Power supply: 24Vdc  
Power Consumption: standby 0.8W, working 3W  
Lock Power Supply: 12Vdc, 280mA (Internal power - Fail secure only)

### Wiring

2-wire  
No polarity

### Dimensions

Dimensions: 176 x 90 x 27mm  
Environment: -20°C to 55°C