## Controlsoft® Solo2

Part Code: CS-AC-3300-PCB

Part Code: CS-AC-3300





The Solo 2 from Controlsoft is a standalone Access Control Unit, providing cost effective access control for two door applications using Wiegand readers.

## **Features & Benefits**

- Standalone Two Door Solution
- Unit includes a Removable Memory Stick to Backup or Copy All User Data
- Supports up to 2000 Users
- Add or remove users via the on-board display and buttons
- Option for "Reader In" or "Reader In and Out" on each door
- Latched or Pulse Mode
- On-board RJ11 Connector for Local Enrolment Reader (Part Code CS-AC-3301)
- AntiPassBack across doors

## **Technical**

- 12Vdc @ 50mA
- 3 Amp Power Supply on Boxed Version
- Removable Terminal Blocks for Ease of Installation
- 4 x Inputs for Request to Exit Buttons and Door Contacts.
- 3 x Relays for Locks and Siren.
- Up to 4 Wiegand Readers (Read In & Out on Both Doors)
- Dimensions (PCB): 104mm x 90mm x 20mm
- Dimensions (Box): 283mm(h) x 283mm(w) x 93mm(d)
- Weight (Box): 3.5Kg
- Operating Temperature: -20°C to +60°C
- Operating Humidity Range: 5% to 95%
- 2 Year Warranty

## www.controlsoft.com

© 2013 Controlsoft Limited. All rights reserved. Controlsoft and the Controlsoft logo are registered trademarks of Controlsoft Limited in Europe, the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

