

DA1100

SecurePoE™ Multispan

- Includes pre-patched Cisco 5-Port Gigabit network switch
- High efficiency power supply providing 100% power availability to each PoE port
- SecurePoE™ is provided in secure enclosures, with monitoring functions and fast cable entries
- Designed to allow installers to connect to PoE powered devices allowing easier installation, set-up and maintenance
- Power status LEDs for quick visual diagnosis of system status
- Network data infrastructure issues do not affect the supply of PoE power
- Further information available at www.Dantech.uk.com

| | | | | | | |
|------|---|-----------|---|----------------|---|------|
| CCTV | – | Intercoms | – | Access Control | – | VOIP |
|------|---|-----------|---|----------------|---|------|

A power over Ethernet multispan power supply with secure enclosure and monitoring. Every SecurePoE™ unit complies with the IEEE 802.3:2012 standard (IEEE 802.3at/IEEE 802.3af). SecurePoE™ units will provide the full 30W of power to every port. All units are housed in secure tamper protected cases.

One, two or four PoE output wall mount versions are available in secure indoor or exterior enclosures. 1U Rack-mount versions are available with 4 PoE ports per unit.

The PoE outputs have LED indication to show if a compatible device is connected and powered. In addition there are SPCO clean contacts for monitoring the power status of each output.

PoE multispan devices combine the reliability of a midspan device with the ease of an endspan unit.

The pre-patched unmanaged switch allows for one data connection (e.g. from network) to be connected to up to 4 PoE powered devices, whilst providing reliable power to these devices.

Multispan units can be located 100 meters away from existing network infrastructure and attached devices can be a further 100 meters from the SecurePoE™ Multispan unit.

| Output | | | | | | | |
|---------------------------------|--|---|---------------------------------|---|---------|---------|---------|
| PoE Ports | <table border="1" style="width: 100%; text-align: center;"> <tr> <td style="width: 25%;">DA1100-IN-1 DA1100-EX-1 -</td> <td style="width: 25%;">DA1100-IN-2 DA1100-EX-2 -</td> <td style="width: 25%;">DA1100-IN-4 DA1100-EX-4 DA1100-RM-4</td> </tr> <tr> <td>1 x 30W</td> <td>2 x 30W</td> <td>4 x 30W</td> </tr> </table> | DA1100-IN-1 DA1100-EX-1 - | DA1100-IN-2 DA1100-EX-2 - | DA1100-IN-4 DA1100-EX-4 DA1100-RM-4 | 1 x 30W | 2 x 30W | 4 x 30W |
| DA1100-IN-1 DA1100-EX-1 - | DA1100-IN-2 DA1100-EX-2 - | DA1100-IN-4 DA1100-EX-4 DA1100-RM-4 | | | | | |
| 1 x 30W | 2 x 30W | 4 x 30W | | | | | |
| Voltage | 55V DC (nominal) | | | | | | |
| Current | Maximum 0.55A (30W) per port | | | | | | |
| Connection type | RJ45 - Plug & play | | | | | | |
| Status indication | LED indication; <i>Flashing = PoE device connected, no power requested</i> <i>On = PoE device connected, power enabled</i> <i>Off = PoE device not detected</i> | | | | | | |
| Compatibility | IEEE 802.3:2012 (IEEE 802.3at & IEEE 802.3af, full backward compatibility) | | | | | | |
| Data rate | DA1100-x-x-G 10BASE-T 100BASE-TX 1000BASE-T (Gigabit) | | | | | | |
| Power class detection | Automatic class 0, 1, 2, 3, 4 detection | | | | | | |
| Mode | Mode B (Delivers power over spare pairs on 10/100 networks only) | | | | | | |
| Internal network switch power | 12V 1A (5.5mm connector) | | | | | | |

DA1100

SecurePoE™ Multispan

Monitoring contacts – (individual output status & unit power fault switching)

| | |
|-----------------------|---|
| Contact configuration | Single pole change over |
| Rating | Maximum switching 30V 1A AC/DC |
| Connection type | Rising clamp PCB terminal block (2.5mm ²) |

Input

| | | | |
|---------------------|--|---------------|---|
| Voltage | 90-270V AC, 47-63Hz | | |
| Power consumption | ≤ 132VA - <i>Built-in active PFC function, PF>0.96</i> | | |
| Connection type | DA1100-IN-x-G | DA1100-EX-x-G | DA1100-RM-4-G |
| | 10mm ² internal terminal block (3 x 1.5mm ² or 2 x 2.5mm ²) | | C14 IEC connector (<i>Kettle lead</i>) |
| Fused | 3A Mains 1" fuse (BS1362) | | 6.3A Mains QB 20 x 5mm Glass fuse |
| Mains on indication | LED indication | | Neon indicator |

Environmental

| | | | |
|-----------------------------|----------------------------|---------------|---------------|
| Operating temperature | -10°C to +40°C | | |
| Storage temperature | -20°C to +50°C | | |
| Operating relative humidity | Maximum 95% non-condensing | | |
| Ingress protection | DA1100-IN-x-G | DA1100-RM-x-G | DA1100-EX-4-G |
| | IP20 | | IP66 |

Dimensions*

| | DA1100-IN-x-G | DA1100-EX-x-G | DA1100-RM-4-G |
|--------------------|--------------------------------|--|--------------------------------|
| Width | 250mm | 280mm | 478mm (19" Rack-mount) |
| Height | 330mm | 340mm | 44mm (1U) |
| Depth | 125mm | 130mm | 380mm (15") |
| Weight | ≤ 2.9Kg | ≤ 2.5Kg | ≤ 5.3Kg |
| Enclosure material | Mild steel | Acrylonitrile Butadiene Styrene (ABS) | Mild steel |
| Finish | Powder coated White RAL9016 | Grey RAL9003 | Powder coated Black RAL9005 |

Other

| | |
|----------------|--------------|
| Estimated MTBF | 50,000 hours |
| CE Approved | Yes |
| Tamper switch | Yes |