

## DA371

**12V DC 1.5A Power supply**  
*Within a mild steel enclosure*

A power supply unit with 1 x 12V DC 1.5A output, which will house and charge one VRLA battery up to 7Ah capacity. This unit comes with two SPCO relays that provide mains fail and low voltage signalling. Typical uses include, powering door access controllers, electronic releases, magnetic locks & CCTV cameras.

Output	
Voltage	12V DC (13.7V)
Current	1.5A
Connection type	PCB terminal block (2mm <sup>2</sup> )
Fused	20 x 5mm 2A quick blow glass fuse
Mains fail signalling contacts	
Contact configuration	Single pole change over (Approximately 30 second delay)
Voltage	Maximum 30V DC
Current	Maximum 1A
Connection type	PCB terminal block (2mm <sup>2</sup> )
Battery low volts signalling contacts	
Contact configuration	Single pole change over (Battery at 9V change over)
Voltage	Maximum 30V DC
Current	Maximum 1A
Connection type	PCB terminal block (2.5mm <sup>2</sup> )
Input	
Voltage	230V AC @ 50Hz (+/- 10%)
Power consumption	< 27VA
Connection type	10mm <sup>2</sup> internal terminal block (3 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup> )
Fused	3A Mains fuse (BS1362)
Mains on indication	LED indication
Environmental	
Operating temperature	-10°C to +40°C
Storage temperature	-20°C to +50°C
Operating relative humidity	Maximum 95% non-condensing
Dimensions*	
Width	210mm
Height	260mm
Depth	80mm
Weight	< 2.8Kg
Enclosure material	Mild steel
Finish	Powder coated RAL9016 (white)
Other	
Estimated operations before failure (MTBF)	50,000 hours
CE Approved	Yes
Recommended battery size	7Ah VRLA

\*(+/- 2mm)