

DA390

24V AC 4A Power supply Within a mild steel enclosure

This multi-purpose metal cased power supply provides 8 x 24V AC 500mA via individually fused outputs.

Manufactured and tested in Britain, this range of power supplies has a five year warranty, allowing installers to fit and forget. It is ideal for where high reliability is required and where companies may have service or maintenance contracts for long periods of time.

Typical uses include powering CCTV cameras and camera housing heaters.

Output	
Voltage	24V AC
Current	8 x 500mA
Connection type	PCB terminal block (2.5mm²)
Fused	20 x 5mm 500mA quick blow glass fuse
Input	
Voltage	DA390 DA390-110V
	230V AC @ 50Hz (+/- 10%) 110V AC @ 50Hz (+/- 10%)
Power consumption	< 125VA
Connection type	10mm² internal terminal block (3 x 1.5mm² or 2 x 2.5mm²)
Fused	3A Mains fuse (BS1362)
Environmental	
Operating temperature	-10°C to +40°C
Storage temperature	-20°C to +50°C
Operating relative humidity	Maximum 95% non-condensing
Dimensions*	
Width	118mm
Height	275mm
Depth	70mm
Weight	< 2.3Kg
Enclosure material	Mild steel
Finish	Powder coated RAL9016 (white)
Other	
Estimated operations before failure (MTBF)	65,000 hours
CE Approved	Yes

*(+/- 2mm)