

## DA442

12V DC 8A / 24V DC 4A power supply  
Within a 19" 2U Rack-mount enclosure

A 19" rack mountable power supply with 12V DC 8A or 24V DC 4A (Model dependant) individually fused and indicated outputs. Typical uses include powering CCTV cameras, camera housing heaters.

Output							
	DA442-4	DA442-8	DA442-16	DA442-2-24	DA442-4-24	DA442-8-24	DA442-16-24
Voltage	12V DC	12V DC	12V DC	24V DC	24V DC	24V DC	24V DC
Current	4 x 2A	8 x 1A	16 x 500mA	2 x 2A	4 x 1A	8 x 500mA	16 x 250mA
Connection type	PCB terminal block (2.5mm <sup>2</sup> )						
Fused	20 x 5mm quick blow glass fuse rated to output current (e.g. DA442-4, 4 x 2A)						
Input							
Voltage	230V AC @ 50Hz (+/- 10%)						
Power consumption	< 125VA						
Connection type	C14 IEC connector ( <i>Kettle lead</i> )						
Fused	6.3A Mains fuse (BS1362)						
Mains on indication	Neon lamp						
Environmental							
Operating temperature	-10°C to +40°C						
Storage temperature	-20°C to +50°C						
Operating relative humidity	Maximum 95% non-condensing						
Dimensions*							
Width	478mm ( <i>19" Rack-mount</i> )						
Height	89mm ( <i>2U Standard rack-mount</i> )						
Depth	248mm						
Weight	< 3.2Kg						
Enclosure material	Mild steel						
Finish	Powder coated black semi-gloss						
Other							
Estimated operations before failure (MTBF)	65,000 hours						
CE Approved	Yes						

\*(+/- 2mm)