

## PRODUCT DATA SHEET FOR DA668/1

### PRODUCT DESCRIPTION

A power supply that provides 1 x 2A 24V DC outputs. Each output is fused and is provided with internal LED indication, the PSU also accepts a wide mains input range. The unit is intended for use with CCTV cameras. Metal Cased.

### PRODUCT SPECIFICATION

#### General Electrical and Mechanical Specification

- Supply Voltage: \_\_\_\_\_ 96 – 250 VAC, 47 - 63Hz
- Current Consumption: \_\_\_\_\_ Max 1.3A
- Colour: \_\_\_\_\_ White
- Size in mm (W x H x D): \_\_\_\_\_ 230 x 145 x 35
- Weight in Kg: \_\_\_\_\_ 1.3 KG
- Packed Size in mm (W x H x D): \_\_\_\_\_ 240 x 150 x 40
- Packed Weight in Kg: \_\_\_\_\_ 1.4 KG
- Case Material: \_\_\_\_\_ Powder coated 1.2mm Mild Steel
- Operating Temperature: \_\_\_\_\_ -10 to + 40 degrees C
- Storage Temperature: \_\_\_\_\_ - 20 to + 50 degrees C
- Operating Relative Humidity: \_\_\_\_\_ 0 – 95%, non condensing.
- MTBF: \_\_\_\_\_ 50'000 Hrs
- CE approved: \_\_\_\_\_ Yes

#### Other Relevant Specification

- Output Voltage: \_\_\_\_\_ 24V DC Regulated
- Current: \_\_\_\_\_ 2A Total
- Recommended Battery Size: \_\_\_\_\_ N/A
- Fan Cooled: \_\_\_\_\_ No
- Tamper Switch: \_\_\_\_\_ No