



Product Data Sheet

DDV1016AM

16 m volumetric Dual Technology/AM motion sensor

Patented Range Gated Radar Technology

Motion sensors of the DD1000 Series incorporate a UTC Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection pattern.

Every motion sensor comes with 4 possible radar ranges selectable via dip switches allowing the detection pattern to be tailored according to the room where the motion sensor is installed.

The radar operates on 5.8GHz frequency and will not interfere with any WIFI networks.



PIR Technology in combination with patented mirror optics

Our patented optical mirror technology gives the advantage of gliding focus, which creates a continuous detection curtain from floor level up to installation height.

Using a four element pyro, so generating 4 volumetric curtains for each of the 9 curtain sets, in combination with our VE-techniques allowed us to create a 16m dual tech motion sensor in a rather small housing

Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within its detection coverage.

But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

Standard Features

- Patented selectable range gated radar technology clearly defining the radar detection border
- PIR technology with patented mirror curtain optics
- Anti-masking variant using Active Infrared and radar technology to protect against sabotage actions outside and inside of the motion sensor
- Intelligent alarm decision based on signal classification of the PIR and radar alarm
- Automatic continuous self diagnostics on all technologies
- Green mode : option to switch off the radar technology when the security system is not armed
- Holding several security approvals including EN Grade III and UL/ULC

DDV1016AM

16 m volumetric Dual Technology/AM motion sensor

Specifications

Detection range	10, 12, 14, 16 m selectable via dip switches
Viewing angle	78°
PIR Optics	9 high density mirror curtains
Microwave frequency	5.8 GHz
Max. microwave output (at 1m)	0.003 μ W/cm ²
Memory function	Yes
Input power	9 to 15 VDC (12V nominal)
Peak-to-peak ripple immunity	2V (at 12 VDC)
Detector start-up time	60 s
Current consumption	10 to 16 mA (10 mA nominal)
Mounting height	1.8 to 3.0 m
Target speed range	0.2 to 3.0 m/s
Alarm/ Tamper relay characteristic	NC, 80 mA 30 VDC, Form A
Fault relay characteristic	NC, 80 mA 30 VDC, Form A
Alarm time	3 s
Operating temperature	-10 to +55° C
Relative humidity	95% max. non-condensing
Weight	120 g
Dimensions (H x W x D)	126 x 63 x 50 mm
IP/IK rating	IP30 IK04
Pry-off tamper	On board

Ordering Information

Part No.	Description
DDV1016AM	16m/50ft, Dual Tech, 9C, AM
SB01	Wall/ceiling mount bracket (\pm 45° horizontal, 0° or -5° vertical)
AMGR2-10	(10 PACK) Anti-mask Grade 2 easy wiring

Ease and flexibility of installation

1. Tolerates wall angle deviation and different mounting heights.
2. Limited loss of coverage when objects are placed in the field of the PIR vision.
3. Easy range setting via dip switches of the range gated radar in order to tailor the detection pattern to your needs.
4. Multiple build-in End-Of-Line resistor values with “easy wiring” option available.
5. Plug-in connector.

Anti-masking (optical and radar)

The use of Active Infrared and radar technology results in a superior anti-masking functionality that supervises the motion sensor on the inside and outside. Radar verification prevents from having unwanted AM alarms caused by e.g. insects. In advanced setting the AM alarm is held until the effective source of the anti-masking (e.g. spray, tape,...) has been removed. Even partial masking – so going beyond the EN Grade III standard – will be detected when in advanced setting.

Other members of the family

This family includes motion sensors with variants in detection range, two types of anti-masking masking technology and Pet Immunity. The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

