# **Digitag LR**

## Hands-Free Access Control



### Range: Digitag LR

Digitag LR is an innovative product range offering users real "hands-free" access control at affordable prices.

Digitag LR is ideally suited for use in hospitals, residential homes, car parks, areas of stock movement or simply where the convenience of hands-free access control is preferred. The range attenuation, together with the ease of installation and the flexibility of being industry compatible has made Digitag LR a leader in this field.

Clever innovation has removed the traditional objections of hands-free active cards & tags (battery life and cost). By providing a changeable battery, the cards & tags do not have a limited life so under normal wear & tear conditions they will provide many years of activity.

A new development is the inclusion of an integral motion sensor (optional) within the card and tag. This ensures that while the card/tag is stationary, no signal will be transmitted therefore prolonging the battery life.

### **Technical specification**

#### Receiver

Voltage 12-30Vdc 40mA Current Frequency 433.92MHz 15M nominal Range Control 1 High/low gain Control 2 10 point attenuator I FD 1 green, 1 red Internal helical Antenna Sensitivity -102dBm

Output 1 Wiegand 26 Bit / Clock &

Data ISO

Output 2 CDVI 1-wire protocol

TX Buffer 20 Tags in field

90 x 60 x 22mm **Dimensions** 

### Transmitter

3V Supply CR2032 Battery 433.92MHz Frequency Modulation FSK 5µW E.r.p

**Dimensions** Card - 85 x 53 x 6mm

> 70 x 35 x 9mm Tag -











Multi-tenant occupancy





#### **Product codes**

**DTRR1434** Digitag LR reader **DTXT0434** Hands-free tag

DTXT0434M Hands-free tag, motion sensor

DTXT5434 Hands-free card

**DTXT5434M** Hands-free card, motion sensor

