



FIRE & SECURITY



EPA-NG/PLUS

Electronic Hold Up Device

The EPA - NG is the most advanced Hold-Up device available on the market today. Packed with innovative features, this electronic unit is a versatile device capable of many functions.



- Second Relay Output (for confirmed operation)
- One or Two Button Operation
- Timed Delay Operation
- LED Indicator
- Latching or Non Latching
- Selectable EOL Settings
- Keyless Reset
- PD6662:2010

Connections	10 PCB Terminals	Temperature Range	-15° C to +40° C
Operation Method	Single or Dual Push Button	Tamper	Cover
Material	ABS	Reset Method	Dual Push
Dimensions mm	85 x 85 x 39	Colours	White / Stainless Steel / Brass
PA Output	Programmable Latching / Non Latching Relay	Confirmed Output	N/C Relay
Voltage Range	12v DC	Standards	EN50131-1 Grade 3 / PD6662:2010 / BS8243:2010
Current	10mA @ 12Vdc	Environmental Class	II
Output Option	N/O or N/C Output / Instant or Delay Programmable		



FireBrand — **2Y-LINK** — CQR MAXIMAL

CQR Fire & Security
125 Pasture Road, Moreton, Wirral, CH46 4TH, UK



Sales: 0151 606 1000 Tech: 0151 606 6311 www.cqr.co.uk info@cqr.co.uk