

Ionisation Smoke Alarm

9V Battery Powered

Model Ei100S

- Dual Ionisation chamber sensor
- Built in Test and Hush buttons
- Low power cell warning
- Kitemarked to BS EN14604:2005
- 5 Year Guarantee



Product Description

The Ei100S is an Ionisation Smoke Alarm, powered by a 9V battery

The alarm gives a fire warning when adequate smoke enters the alarm.

Operation

- The "Test" button will perform a self test and sound the horn
- The "Hush" button will silence false alarms. The unit will then beep once every 40 seconds for 10 minutes to indicate it is in "Hush" mode
- The alarm will emit a beep every 40 seconds to indicate that the battery is depleted and needs replacing

Technical Specification

1. The Smoke Alarm carries the BSI Kitemark to indicate type testing to BS EN14604:2005. It will meet the requirements of Grade F systems as defined in BS5839: Pt.6:2004. It carries the CE mark to indicate conformance to Electromagnetic Compatibility Directives.
2. Dual ionisation chamber sensor, with corrosion resistant electrodes, and insect resistant cover.
3. Built in sounder giving a minimum sound output of 85dB(A) at 3m. Frequency is in the range 2200/2800Hz. The diameter of the piezo disc in the sounder measures 40mm, and has wire contacts soldered directly on to the piezo disc. The sounder includes a resonator or "trumpet" 30mm in length, which reaches to the lid of the outer casing in order to amplify the sound.
4. "Test" button to simulate the effect of smoke and tests sensor, electronics and horn.
5. "Hush" button - Silences unwanted alarms for up to 10 minutes and beeps every 40 seconds to warn that alarm is in 'Hush' mode. Automatically resets.
6. Automatic Self-Test: Smoke chamber is tested every 40 seconds and unit beeps if a fault is detected.
7. Automatic reset facility in that when smoke clears from the alarm sensor the unit will reset automatically.
8. Battery fitted with reliable snap fit connector, which prevents the battery being connected up the wrong way round. It also overcomes the problem of creepage.
9. Low battery warning signal, beeps every minute for 30 days - when replacement battery is required.
10. Airspeed: No effect.
11. Ambient Temperature Range: 4°C to 40°C. Humidity Range: 0 to 90% relative humidity.
12. Dimensions: 140 x 125 x 46mm. Weight inclusive of packaging: 220g.
13. Manufactured in Ireland
14. 5 year guarantee



Mile End Business Park, Oswestry, Shropshire SY10 8NN

Tel. 0870 758 4000

Fax. 0870 758 4010

www.aico.co.uk

E & OE Our policy is one of continuous improvement.

We reserve the right to amend designs and specifications without prior notice.

Ei100S DataSht Rev 0 03.08.10

Aico Ltd is a wholly owned subsidiary of Ei Electronics