United Technologies
Climate | Controls | Security

FA350WY
LED Visual Indicator, White Shallow Base, Yellow Lens

General

The FA350WY is a general purpose LED visual indicator for alarm applications. It features a special base containing all wiring connections and allows for easy removal/placement of the device and base.

Easy and Fast Installation

The FA350WY allows faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these devices use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a "twist and click" action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

Efficient and versatile

A mechanism for locking the devices to the base may be activated if required. Once activated, a special tool is required to remove the device from the base.
The FA350WY utilises a full faced translucent case, giving a much larger lens area and a greater spread of light.

Details

- Low current consumption
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- High efficiency LED's

FA350WY
LED Visual Indicator, White Shallow Base, Yellow Lens

Technical specifications

Electrical

Operating voltage	17 to 60 VDC

VID

Flash frequency	1 Hz, 60 flashes/min

Physical

Net weight	215 g

Environmental

Operating temperature	-25 to +70°C
Environment	Indoor
IP rating	IP21

Operation

Continuous

Supply voltage

17 - 60 VDC

Current consumption

5mA

Flash rate

60 / min

Line monitoring input

Polarised input

Housing

High impact polycarbonate

Ingress protection

IP21

Operating temperature

-25°C to +70°C

Dimensions (Ø x D)

Shallow base	100 x 81 mm

Weight

215g

Colour

Base	White
Lens	Yellow/Amber

United Technologies
Climate | Controls | Security