



## FAC350

Conventional VAD, Shallow base, Ceiling mount - RED flash

### General

---

The FAC350 is a general purpose ceiling mount LED beacon for fire alarm applications. It features a special base containing all wiring connections and allow for easy removal/placement of the device. With an EN54-23 approved coverage pattern of C-3-8.9, each FAC350 may be mounted up to 3m high and provide a 8.9m cylinder diameter coverage. A room size of 6.3 x 6.3m square room may therefore be covered with a single device.

### Easy and Fast Installation

---

The FAX350 beacons allow faster installation and maintenance thanks to an innovative mounting base. Dispensing with the need for locking screws, these beacons use TimeSaver™ bases from the 630 series detectors. Heads are simply locked onto the base with a “twist and click” action, allowing fitting or removal at any time because the base is the only component that needs to be wired. As the cabling requirement is reduced, commissioning time and costs are naturally reduced as well.

### Efficient and versatile

---

The FAX350 beacons utilise a specially designed lens giving a uniformed light output over the specified coverage area. The flash rate of the beacon may be adjusted during installation, with a selection of 0.5Hz or 1Hz.

The mechanism for locking the device to the base may be activated if required. Once activated, a special tool is required to remove the beacon from the base.



### Standard Features

---

- Automatic synchronisation
- Anti-Tamper locking mechanism
- Shallow mouting base
- Wiring directly to base
- Flash rate selectable

# FAC350

Conventional VAD, Shallow base, Ceiling mount - RED flash

## Specifications

Operation	Continuous
Supply voltage	17 - 60 VDC
Current consumption	20mA @ 0.5 Hz / 40mA @ 1 Hz
Flash rate	0.5Hz or 1Hz
Automatic synchronisation	Phased start
Line monitoring input	Polarised input
Housing	High impact polycarbonate
Ingress protection	IP21
Operating temperature	-25°C to +70°C
Humidity	5% to 95%
Dimensions (Ø x D)	
Shallow base	100 x 81 mm
Weight	215g
Housing colour	Red
Flash colour	Red
EN54-23 rating	
Light coverage	C-3-8.9
Mounting position	Ceiling
Mounting height	up to 3 m
Floor coverage	up to 8.9 m diameter

## Ordering Information

Part No.	Description
FAC350	Conventional VAD, Shallow base, Ceiling mount - RED flash

### EN54-23 Coverage: C-3-8.9

